

ENDURE™ AIR BRAKE TUBING

Lasts Longer - Retains its FLEXIBILITY longer in both Heat & Cold!



**NEW
PRODUCT**

Features & Benefits:

More Flexible & Retains Flexibility Longer!

Kuri Tec® Endure™ retains its flexibility longer than traditional nylon tubing in harsh **heat, cold and oil** conditions. Easy to install – fits tight corners.

Industry Leading IMPACT Strength and Vibration Cracking Resistance.

The Kuri Tec® Endure™ engineered formulation retains its flexibility and resists impact cracking in both high **heat** and sub-zero **cold** weather conditions; providing longer service life than traditional nylon tubing in these harsh conditions.

Exceeds Industry Performance Standards.

Kuri Tec® Endure™ far surpasses traditional nylon tubing for heat aging and heated oil aging, while retaining its superior formulation features and flexibility!

Applications:

- Truck, bus and commercial vehicle air brake systems.
- Trailer air brake systems.
- Auxiliary air systems.

Properties:

- Heat, light and UV stabilized.
- Thermoformable.
- Available in various colors.

Compliances:

- Meets DOT FMVSS 106.
- Meets performance requirements of SAE J844.

Service Temperature Range:

-85°F (-65°C) to +200°F (+93°C)





Kuri Tec® Endure™ utilizing polyester compound materials, offers a superior service temperature range than traditional nylon tubing which contributes to longer service life.

One-Piece
Spool Lengths

Endure™ Non-Reinforced Air Brake Tubing — Type A

Nominal Specifications

Series No.	Size Code	Nominal OD (in.)	Nominal ID (in.)	Nominal Wall (in.)	Minimum Burst Pressure at 70°F	Standard Lengths		Approx. Package Weight		Minimum Bend Radius at 70°F
						Spool	Coil	Spool	Coil	
251XX	02	1/8	0.079	0.023	1,000 psi	2,000 ft	100 ft	8.0 lbs	0.4 lbs	0.37"
	02.5	5/32	0.092	0.032	1,200 psi	1,000 ft	100 ft	7.0 lbs	0.7 lbs	0.50"
	03	3/16	0.117	0.035	1,200 psi	1,000 ft	100 ft	9.5 lbs	1.0 lbs	0.75"
	04	1/4	0.170	0.040	1,200 psi	1,000 ft	100 ft	14.5 lbs	1.5 lbs	1.00"
	05	5/16	0.232	0.040	1,000 psi	500 ft	100 ft	9.5 lbs	1.9 lbs	1.25"

Color Codes (XX): BK = Black, BL = Blue, GR = Green, OR = Orange, RD = Red, YE = Yellow

Endure™ Reinforced Air Brake Tubing — Type B

Nominal Specifications

Series No.	Size Code	Nominal OD (in.)	Nominal ID (in.)	Nominal Wall (in.)	Minimum Burst Pressure at 70°F	Standard Lengths		Approx. Package Weight		Minimum Bend Radius at 70°F
						Spool	Coil	Spool	Coil	
151XX	06	3/8	0.251	0.062	1,400 psi	500 ft	100 ft	17.0 lbs	3.4 lbs	1.50"
	08	1/2	0.376	0.062	950 psi	500 ft	100 ft	23.0 lbs	4.6 lbs	2.50"
	10	5/8	0.441	0.094	900 psi	250 ft	100 ft	22.0 lbs	8.8 lbs	3.00"
	12	3/4	0.566	0.094	850 psi	250 ft	100 ft	27.0 lbs	10.8 lbs	3.50"

Color Codes (XX): BK = Black, BL = Blue, GR = Green, OR = Orange, RD = Red, YE = Yellow

The Endure™ and Kuri Tec® trademarks contained in this publication are trademarks of Kuriyama of America, Inc.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

PLEASE REFER TO CURRENT KURIYAMA TERMS, CONDITIONS AND LIMITED WARRANTY OF SALES ISSUED 9/2005



Kuriyama of America, Inc.

Headquarters, Sales Office and Warehouse Location

360 E. State Parkway • Schaumburg, IL 60173-5335

Phone: (847) 755-0360 • Toll-free FAX: (800) 800-0320 • International FAX: (847) 885-0996

Web Site: www.kuriyama.com E-Mail: sales@kuriyama.com

Visit us
www.kuriyama.com
on the Web!



SOUTHWEST WAREHOUSE
KURIYAMA OF AMERICA, INC.
HOUSTON
531 PORTWALL ST., SUITE 100
HOUSTON, TX 77029
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214

WESTERN WAREHOUSE
KURIYAMA OF AMERICA, INC.
SANTA FE SPRINGS
10749 SHOEMAKER AVE.
SANTA FE SPRINGS, CA 90670-4039
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll Free FAX: (800) 326-8940

SOUTHEAST WAREHOUSE
1580 BIG SHANTY DR. NW
KENNESAW, GA 30144-7040
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
Web Site: www.fortneysales.com
E-Mail: sales@fortneysales.com

EASTERN WAREHOUSE
EASTERN RUBBER & PLASTICS CO., INC.
RT. 537 PLUMSTED INDUSTRIAL PARK
NEW EGYPT, NJ 08533-0248
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
Web Site: www.easternrubber.com
E-Mail: sales@easternrubber.com

IN MEXICO:

KURIYAMA DE MEXICO, S. DE R.L. DE C.V., CARRETERA MIGUEL ALEMÁN KM. 14.8, PARQUE INDUSTRIAL HASNA, APODACA (MONTERREY), N.L., 66600, MEXICO

Tel: (81) 1086-1870 o 71 • Toll-Free (within Mexico) 01-800-822-52-00 • FAX: (81) 1086-1869

Internet: www.kuriyama.com • Correo Electronico: ventas@kuriyama.com