

15CA Eclipse Air brake coil

Meets: SAE J844 Type B, DOT-FMVSS 106, (49 FR571.106)



# Part number	Description	Valve pigtail length		Male ends				Working Length	
		mm	in	Valve		Gladhand		m	ft
15CA12-12	15' WL abt coil set w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	4,6	15.00
15CA48-12	15' WL abt coil set w/ 48" pigtails	1.219,2	48.00	12,7	0.50	12,7	0.50	4,6	15.00
15CAR12-12	15' WL single, red abt coil w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	4,6	15.00
15CAB12-12	15' WL single, blue abt coil w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	4,6	15.00
15CAR48-12	15' WL single, red abt coil w/ 48" pigtails	1.219,2	48.00	12,7	0.50	12,7	0.50	4,6	15.00
15CAB48-12	15' WL single, blue abt coil w/ 48" pigtails	1.219,2	48.00	12,7	0.50	12,7	0.50	4,6	15.00
12CA12-12	12' WL abt coils set w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	3,7	17.00
12CAR12-12	12' WL single, red abt coil w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	3,7	17.00
12CAB12-12	12' WL single, blue abt coil w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	3,7	17.00
20CA12-12	20' WL abt coil set w/ 12" pigtails	304,8	12.00	12,7	0.50	12,7	0.50	6,1	20.00

Construction

Tube: Synflex® Eclipse air brake tubing, 100% polyamide

Reinforcement: Polyester yarn

Brass end fittings with corrosion resistant spring guards

Operating parameters

-54°C to +93°C
(-65°F to +200°F)

Application

- Articulating connections for air brake line systems (connections between towed and towing motor vehicle)
- Tractor-to-trailer air connections used in extremely low temperatures

Features

- Superior abrasion resistance
- Excellent return and coil memory
- Enhanced flexibility and extension
- Brass end fittings with corrosion resistant spring guards

3SCE Eclipse Fifth-wheel slider coil

Meets: SAE J844 Type B, DOT-FMVSS 106, (49 FR571.106)



# Part number	Valve pigtail length		End fitting	Working length		Retracted length	
	mm	in		mm	ft	mm	in
3SCE-0303304-033	88,9	3.50	None	1.371,6	54.00	254,0	10.00
3SCE-0303304-166	88,9	3.50	1/4" male pipe	1.371,6	54.00	254,0	10.00

Construction

Tube: Synflex Eclipse air brake tubing, 100% polyamide

Reinforcement: Polyester yarn

Brass end fittings with corrosion resistant spring guards

Operating parameters

-54°C to +93°C
(-65°F to +200°F)

Application

- Articulating connections for air brake line systems (connections between towed and towing motor vehicle)
- Tractor-to-trailer air connections used in extremely low temperatures

Features

- Superior abrasion resistance
- Excellent return and coil memory
- Enhanced flexibility and extension