


Adapters and tube fittings

SAE O-Ring boss to 37° flare

J

SAE O-Ring boss to 37° flare


SAE O-Ring boss (adj.)/37° flare



Part no. 2061-(Dash size) (Ref. SAE 070320)

| Dash size | Tube O.D. | | Thread T1 | Thread T2 | A | | B | |
|-----------|-----------|------|-----------|-----------|------|------|------|------|
| | mm | in | | | mm | in | mm | in |
| 4-4S | 6,3 | 0.25 | 7/16-20 | 7/16-20 | 26,7 | 1.05 | 18,3 | 0.72 |
| 6-4S | 6,3 | 0.25 | 9/16-18 | 7/16-20 | 29,0 | 1.14 | 20,8 | 0.82 |
| 6-6S | 9,6 | 0.38 | 9/16-18 | 9/16-18 | 29,0 | 1.14 | 21,1 | 0.83 |
| 6-8S | 12,7 | 0.50 | 9/16-18 | 3/4-16 | 30,5 | 1.20 | 24,9 | 0.98 |
| 8-6S | 9,6 | 0.38 | 3/4-16 | 9/16-18 | 33,0 | 1.30 | 22,1 | 0.87 |
| 8-8S | 12,7 | 0.50 | 3/4-16 | 3/4-16 | 33,0 | 1.30 | 24,9 | 0.98 |
| 8-10S | 16,0 | 0.63 | 3/4-16 | 7/8-14 | 34,5 | 1.36 | 28,2 | 1.11 |
| 10-8S | 12,7 | 0.50 | 7/8-14 | 3/4-16 | 38,6 | 1.52 | 25,1 | 0.99 |
| 10-10S | 16,0 | 0.63 | 7/8-14 | 7/8-14 | 38,6 | 1.52 | 28,2 | 1.11 |
| 10-12S | 19,0 | 0.75 | 7/8-14 | 1 1/16-12 | 39,9 | 1.57 | 32,5 | 1.28 |
| 12-8S | 12,7 | 0.50 | 1 1/16-12 | 3/4-16 | 43,9 | 1.73 | 26,4 | 1.04 |
| 12-10S | 16,0 | 0.63 | 1 1/16-12 | 7/8-14 | 43,9 | 1.73 | 29,5 | 1.16 |
| 12-12S | 19,0 | 0.75 | 1 1/16-12 | 1 1/16-12 | 43,9 | 1.73 | 32,5 | 1.28 |
| 12-16S | 25,4 | 1.00 | 1 1/16-12 | 1 5/16-12 | 47,2 | 1.86 | 37,3 | 1.47 |
| 14-14S | 22,3 | 0.88 | 1 3/16-12 | 1 3/16-12 | 47,2 | 1.86 | 36,8 | 1.45 |
| 16-12S | 19,0 | 0.75 | 1 5/16-12 | 1 1/16-12 | 47,2 | 1.86 | 36,1 | 1.42 |
| 16-16S | 25,4 | 1.00 | 1 5/16-12 | 1 5/16-12 | 47,2 | 1.86 | 37,3 | 1.47 |
| 16-20S | 31,7 | 1.25 | 1 5/16-12 | 1 5/8-12 | 48,5 | 1.91 | 40,4 | 1.59 |
| 20-16S | 25,4 | 1.00 | 1 5/8-12 | 1 5/16-12 | 48,5 | 1.91 | 39,1 | 1.54 |
| 20-20S | 31,7 | 1.25 | 1 5/8-12 | 1 5/8-12 | 48,5 | 1.91 | 40,4 | 1.59 |

SAE O-Ring flare (adj.)/37° flare



Part no. 206209-(Dash size)

| Dash size | Tube O.D. | | Thread T1 | Thread T2 | A | | B | |
|-----------|-----------|------|-----------|-----------|------|------|------|------|
| | mm | in | | | mm | in | mm | in |
| 4-4S | 6,3 | 0.25 | 7/16-20 | 7/16-20 | 43,9 | 1.73 | 22,6 | 0.89 |
| 6-6S | 9,6 | 0.38 | 9/16-18 | 9/16-18 | 52,8 | 2.08 | 26,9 | 1.06 |
| 8-8S | 12,7 | 0.50 | 3/4-16 | 3/4-16 | 63,0 | 2.48 | 31,8 | 1.25 |
| 8-10S | 16,0 | 0.63 | 3/4-16 | 7/8-14 | 64,0 | 2.52 | 36,8 | 1.45 |
| 10-8S | 12,7 | 0.50 | 7/8-14 | 3/4-16 | 54,9 | 2.16 | 33,8 | 1.33 |
| 10-10S | 16,0 | 0.63 | 7/8-14 | 7/8-14 | 73,4 | 2.89 | 36,8 | 1.45 |
| 12-12S | 19,0 | 0.75 | 1 1/16-12 | 1 1/16-12 | 84,8 | 3.34 | 42,2 | 1.66 |
| 16-16S | 25,4 | 1.00 | 1 5/16-12 | 1 5/16-12 | 94,5 | 3.72 | 46,0 | 1.81 |