


SAE 37° flare

Union




Part no. 259-2027-(Dash size)

Dash size	Tube O.D.		Thread T1	Thread T2	A	
	mm	in			mm	in
4-4	6,3	0.25	7/16-20	7/16-20	34,8	1.37
6-4	6,3	0.25	9/16-18	7/16-20	35,6	1.40
6-6	9,6	0.38	9/16-18	9/16-18	35,8	1.41
8-6	9,6	0.38	3/4-16	9/16-18	38,6	1.52
8-8	12,7	0.50	3/4-16	3/4-16	41,1	1.62
16-16	25,4	1.00	1 5/16-12	1 5/16-12	57,2	2.25
20-20	31,7	1.25	1 5/8-12	1 5/8-12	61,7	2.43
24-24	38,1	1.50	1 7/8-12	1 7/8-12	69,8	2.75

SAE O-Ring boss to SAE 37° flare

Straight thread short connector



Part no. 259-202702-(Dash size)

Dash size	Tube O.D.		Thread T1	Thread T2	A	
	mm	in			mm	in
4-4	6,3	0.25	7/16-20	7/16-20	31,2	1.23
4-6	9,6	0.38	7/16-20	9/16-18	32,3	1.27
6-4	6,3	0.25	9/16-18	7/16-20	32,8	1.29
6-6	9,6	0.38	9/16-18	9/16-18	33,0	1.30
6-8	12,7	0.50	9/16-18	3/4-16	36,6	1.44
8-6	9,6	0.38	3/4-16	9/16-18	35,1	1.38
8-8	12,7	0.50	3/4-16	3/4-16	37,6	1.48
12-12	19,0	0.75	1 1/16-12	1 1/16-12	50,0	1.97
12-16	25,4	1.00	1 1/16-12	1 5/16-12	51,8	2.04
16-12	19,0	0.75	1 5/16-12	1 1/16-12	50,5	1.99
16-16	25,4	1.00	1 5/16-12	1 5/16-12	51,8	2.04
16-20	31,7	1.25	1 5/16-12	1 5/8-12	59,2	2.33
20-16	25,4	1.00	1 5/8-12	1 5/16-12	53,9	2.12
20-20	31,7	1.25	1 5/8-12	1 5/8-12	55,2	2.17
20-24	38,1	1.50	1 5/8-12	1 7/8-12	64,3	2.53
24-20	31,7	1.25	1 7/8-12	1 5/8-12	56,9	2.24
24-24	38,1	1.50	1 7/8-12	1 7/8-12	60,2	2.37