







Cold Flex[™]

CF[™] Series Extra Heavy Duty Low Temperature PVC Suction Hose

General Applications:

- Extreme cold conditions
- Irrigation lines
- Material handling standard duty
- Pumps, rental and construction dewatering
- Pumps, trash
- Slurry handling
- Water suction heavy duty

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

-40°F (-40°C) to +150°F (+65°C)*

Features and Advantages:

- **Superior Vacuum Rating** Our toughest and most durable liquid suction hose! Extremely thick hose tube and extra large helix provide for a tough, durable hose with all sizes rated to full vacuum (at 68°F).
- Cold Flex[™] Materials Hose remains flexible in severe sub-zero temperatures.
- **Convoluted Outer Cover –** Provides increased hose flexibility.
- **Static Dissipative Tube** Specially formulated to help prevent the build-up of static electricity for added safety and help keep material flowing smoothly.
- Phthalate Free

Nominal Specifications Working Vacuum Min. Bending Standard ID OD Pressure (psi) Rating Hg (in) Series Radius Length Weight (in) (mm) (in) (mm) 68°F 104°F 68°F 104°F at 68°F (in) (fť) (lbs/ft) Number CF150 1 - 1/238.1 1.84 46.7 100 Full 28 65 3 100 0.40 CF200 2 50.8 2.41 61.2 100 Full 28 4 100 0.75 65 2 - 1/2CF250 63.5 2.93 74.5 90 55 Full 28 6 100 0.99 CF300 3 76.2 3.59 91.2 80 50 Full 28 7 100 1.34 CF400 35 4 101.6 4.67 118.6 65 Full 28 11 100 2.15 CF600 6 152.4 6.87 174.4 50 25 Full 28 18 100/50/20 3.76 CF800[†] 8 204.8 9.13 232.0 35 15 Full 26 24 20 5.92

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.

PHTHALATE FREE⁽¹⁰⁾, ROHS⁽¹¹⁾

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.