



## DJ Series

### Double Jacket “Contractor Grade” Coupled with Male and Female Aluminum Rocker Lug Couplings

#### General Applications:

- Heavy duty equipment or pump rental
- Hydrant-to-truck water supply line
- Municipal washdown
- Ship deck washdown

#### Construction:

Double jacket with 100% polyester yarn. Water and mildew-resistant cover, will not rot, even if the hose is stored wet.

#### Service Temperature Range:

-25°F (-31°C) to +185°F (+85°C)

#### Features & Advantages:

- **Versatile Natural Rubber Tube** – Exhibits a good combination of strength and extreme flexibility for ease-of-use.
- **Wide Service Temperature Range** – Hose may be used in a wide range of service temperature ranges from -25°F to +185°F.
- **Double Jacket** – Double jacket provides additional external abrasion resistance.
- **Compact Design** – Flat hose design rolls up into tight coils for easy storage and transport, takes up less space than other hoses.
- **Storage/Shipping Carton** – Hoses are individually packaged in cartons for ease of handling and shipping.

## Nominal Specifications

Part Number	Size		Length (ft)	Thread Type	Max. Working Pressure (psi) at 68°F	Weight Each (lbs)
	(in)	(mm)				
DJ150NSTX50	1 1/2	38.1	50	NST	200	14
DJ150NPSHX50	1 1/2	38.1	50	NPSH	200	14
DJ250NSTX50	2 1/2	63.5	50	NST	200	23
DJ250NPSHX50	2 1/2	63.5	50	NPSH	200	23

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

