



FC693

Premium EPDM
two wire braided hose

by Danfoss
FC693-04
6,4 mm (0,25 in)
DN6
 345 BAR (5000 PSI)
 -40°C to +79°C
-40°F to +175°F
1A

Typical application:

Ground support equipment (GSE), industrial phosphate ester-based fluids, water glycol systems

Agency specifications:

Hose construction:	Inner tube: EPDM	Reinforcement: Two wire briad	Cover: EPDM
Operating temperature:	-40°C to +79°C (-40°F to +175°F)		
Qualified fittings:	1A series		

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
FC693-04	6,4	0.25	15,1	0.59	345,0	5,000	1380	20,000	102	4.00	0,37	0.25
FC693-06	9,5	0.38	19,2	0.75	275,0	4,000	1100	16,000	127	5.00	0,54	0.36
FC693-08	12,7	0.50	22,1	0.87	240,0	3,500	960	14,000	178	7.00	0,60	0.40