



The following BOCK Fittings are MTO.
The Nipple and the Socket must be ordered separately.
Please contact Eaton Customer Service to determine leadtime.

BOCK, straight




PART NUMBER	HOSE HEX SIZE	TUBE SIZE	THREAD SIZE	A		HOSE CUT-OFF FACTOR		HOLE DIAMETER		NIPPLE (METRIC)	PART # SOCKET	SOCKET HEX (METRIC)
				MM	IN	MM	IN	MM	IN			
GA25126-16	16	16	-	96,0	3.78	66,5	2.62	17,5	.69	24	G1212-16K	36
GA25126-20	20	20	-	101,5	4.00	68,0	2.68	24,2	.95	36	G1212-20K	46
GA25126-24	24	24	-	96,0	3.78	53,4	2.10	29,5	1.16	46	G1212-24K	50

BOCK, 45° tube elbow



PART # FOR HOSE NIPPLE	HOSE SIZE	TUBE SIZE	THREAD SIZE	A		HOSE CUT-OFF FACTOR		DROP DIM.		HOLE DIAMETER		NIPPLE HEX (METRIC)	PART # SOCKET	SOCKET HEX (METRIC)
				MM	IN	MM	IN	MM	IN	MM	IN			
GA25127-16	16	16	-	114,1	4.49	84,6	3.33	46,1	1.81	17,5	.69	24	G1212-16K	36
GA25127-20	20	20	-	122,6	4.83	89,1	3.51	46,1	1.81	24,2	.95	36	G1212-20K	46
GA24127-24	24	24	-	134,7	5.30	99,7	3.93	38,0	1.50	29,5	1.16	46	G1212-24K	50

BOCK, 90° tube elbow



PART # FOR HOSE NIPPLE	HOSE SIZE	TUBE SIZE	THREAD SIZE	A		HOSE CUT-OFF FACTOR		DROP DIM.		HOLE DIAMETER		NIPPLE HEX (METRIC)	PART # SOCKET	SOCKET HEX (METRIC)
				MM	IN	MM	IN	MM	IN	MM	IN			
GA25128-16	16	16	-	81,5	3.21	52,0	2.05	55,4	2.18	17,5	.69	24	G1212-16K	36
GA25128-24	24	24	-	109,5	4.31	74,5	2.93	90,5	3.56	29,5	1.16	46	G1212-20K	50