Redi-Lock® 300



Non-Conductive 300 PSI Push-On Hose

General Applications:

- Air tools
- Low pressure pneumatic systems
- Robotic welders
- · Water, oil and mild chemical solutions
- * Not recommended for unleaded gasoline

Construction:

- Cover Black Nitrile/PVC, RMA Class A oil resistant.
- Reinforcement Aramid spiral yarn.
- Tube Black Nitrile, RMA Class A oil resistant.

Service Temperature Range:

-30°F (-34°C) to +180°F (+82°C)

Features and Advantages:

- Non-Conductive Tested to one (1) MEGOHM per inch resistance minimum.
- MSHA approved flame resistant cover.
- Easy to couple.
- Long lengths on reels.

Branding:

REDI-LOCK NON-CONDUCTIVE 300 PSI <size> MADE IN USA MSHA1C - 114/03

Packaging:

Maximum 2 pcs. on reel.

1/4" - 5/8" ID hoses supplied on plastic reels, 3/4" ID hoses supplied on wooden reels.

Note: For Push-On Fittings and Quick Disconnect Couplings refer to pages 15-17 of this catalog.





Nominal Specifications						
Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
REDI-LOC-04X700	Black	1/4	1/2	300	700	70
REDI-LOC-06X700	Black	3/8	5/8	300	700	91
REDI-LOC-08X700	Black	1/2	3/4	300	700	112
REDI-LOC-10X700	Black	5/8	29/32	300	700	161
REDI-LOC-12X700	Black	3/4	1 1/32	300	700	182

Note: Cut lengths for this product are available from our Kuriyama Schaumburg, IL Warehouse location. Please call (847) 755-0360 or e-mail: sales@kuriyama.com for more information.