













UFC[™] Series

Heavy Duty Polyurethane Lined Material Handling Hose

General Applications:

- Agricultural dry fertilizer
- Air seeder lines
- Industrial vacuum equipment
- Material handling heavy duty abrasive
- Milling machine scrap recovery
- Plastic processing equipment
- Shot blast recovery

Construction: PVC cover with polyurethane liner and rigid PVC helix.

Service Temperature:

-40°F (-40°C) to +150°F (+65°C)*

Features and Advantages:

- Thick Abrasion Resistant Polyurethane Liner –
 Designed for dry applications where severe abrasion
 is a factor. Provides for longer hose life and lower
 operating costs versus rubber or PVC hoses.
- Static Dissipative Cover Specially formulated to help prevent the build-up of static electricity for added safety and to help keep material flowing smoothly.

Nominal Specifications

Phthalate Free







- Transparent Construction "See-the-flow." Allows for visual confirmation of material flow.
- "Cold-Flex" Materials Hose remains flexible in sub-zero temperatures.
- Convoluted Outer Cover Provides increased hose flexibility.
- Oil Resistant Polyurethane Liner Resists most animal and petroleum based oils.

Nonmai opecifications											
Series	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius	Standard Length	Weight
Number	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F	at 68°F (in)	(ft)	(lbs/ft)
UFC150	1-1/2	38.1	1.85	47.0	50	25	Full	28	2	100	0.42
UFC200	2	50.8	2.40	61.0	40	20	Full	28	3	100	0.59
UFC250	2-1/2	63.5	3.07	78.0	40	20	Full	28	3	100	0.80
UFC300	3	76.2	3.64	92.5	40	20	Full	28	4	100	1.18

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

120.9

4.76

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.

101.6

PHTHALATE FREE⁽¹⁰⁾, RoHS⁽¹¹⁾

UFC400

1.95

100